



**AVC 016 PA, angle valve,
pneumatic, with PI, without PV**






AVC 016 PA, angle valve, pneumatic, with PI, without PV

- Bellows-sealed
- With visual position indicator
- Normally closed (n. c.)
- Service life: 10 million operating cycles

Dimensions



Technical Data	AVC 016 PA, angle valve, pneumatic, with PI, without PV
Feedthrough	Stainless steel Bellows
Seal	FKM
Position indicator	Included
Housing	Aluminum
Actuator	Pneumatic
Tightness	$1 \cdot 10^{-10}$ Pa m ³ /s $1.33 \cdot 10^{-8}$ Torr l/s $1 \cdot 10^{-8}$ mbar l/s
Conductance value with molecular flow	5 l/s
Operating pressure min.	$1 \cdot 10^{-8}$ hPa $7.5 \cdot 10^{-9}$ Torr $1 \cdot 10^{-8}$ mbar
Pressure max. (absolute)	2,000 hPa 1,500 Torr 2,000 mbar
Bakeout temperature: actuator, pilot valve	50 °C 122 K -223.15 °F
Bakeout temperature: housing	80 °C 176 K -193.2 °F
Differential pressure in closing direction	5,000 hPa 3,750 Torr 5,000 mbar
Differential pressure in opening direction	2,000 hPa 1,500 Torr 2,000 mbar
Weight	0.49 kg 1.08 lb
Compressed air volume	4 cm ³
Operating pressure min.	$1 \cdot 10^{-8}$ hPa
Pressure max. (absolute)	2,000 hPa
Connection flange	DN 16 ISO-KF
Closing/opening time	100 ms/100 ms
Compressed air (overpressure)	4 000 – 8 000 hPa
Differential pressure in closing direction	5,000 hPa
Differential pressure in opening direction	2,000 hPa
Weight	0.49 kg

Order number	AVC 016 PA, angle valve, pneumatic, with PI, without PV
AVC 016 PA, angle valve, pneumatic, with PI, without PV	PF A36 003

Accessories	AVC 016 PA, angle valve, pneumatic, with PI, without PV
Set of seals for AVC/DVC valve, DN 16 ISO-KF	PT 130 300 -T
Corrugated bellows, complete for AVC/DVC valve, DN 16 ISO-KF	PT 130 303 -T
Hood, complete for AVC/DVC valve PA/PX, DN 16 ISO-KF	PT 130 306 -T
Cable socket, 6-pin +PE, angled, for valve AVC, DVC, EVB with PI and/or PV	PT 130 309 -T

Your Success. Our Passion.

We give our best for you every day –
worldwide!

Are you looking for an optimum vacuum solution?

Talk to us:
Pfeiffer Vacuum GmbH
Germany
T +49 6441 802-0

Or scan the barcode, to visit our web page:



<https://webportal.pfeiffer-vacuum.com/global/en/contact>



Errors and/or changes excepted. - 5/29/2024

Follow Us On Social Media
#pfeiffervacuum



PFEIFFER  **VACUUM**

www.pfeiffer-vacuum.com